



NI02-1000whWLMi



NI01-500whWLMi

iSitePower-M mini



WL-2400 Pro: New series, unique design

WL-2400 Pro supports DC, AC, and USB connections, ensuring uninterrupted power whether you're working, resting, or playing.

Whether you're on an outdoor adventure, camping, or facing a sudden power outage, WL-2400 Pro can reliably provide stable electricity.

| | | | |
|-------------|---------------------------|---|---|
| Basic Spec. | Weight | 5.4kg | 9.4kg |
| | Dimensions | 194.8(L)*210(W)*180.9(H)mm | 290.1(L)*210(W)*180.9(H)mm |
| Battery | Capacity | 532.8Wh | 1065.6Wh |
| Input | Grid | 20V/5A, MAX 100W | 20V/5A, MAX 140W |
| | PV | 17.5-24VDC, MAX 120W(MPPT) | 17.5-24VDC, MAX 150W(MPPT) |
| | Type-c | 5V/9V/12V/20V3A, MAX 60W | |
| | Car charging | 12.6-15V/8A, MAX 100W | |
| Output | AC output | 2 x AC socket 300W Pure Sine Wave 220V/50Hz/60Hz | 2 x AC socket 700W Pure Sine Wave 220V/50Hz/60Hz |
| | DC output | 2 x DC(5521), 12.6V/5A | |
| | Car charger output | 1 x car charger port, 12.6V/10A | |
| | USB | 2 x USB-A, 5V/2.1A | |
| | Type-c | 1x Type-C, 5V/9V/12V/20V3A, MAX 60W | |
| Temp. | Charge operation temp. | 0~40°C | |
| | Discharge operation temp. | -10~45°C | |
| | Storage temp. | -20~45°C | |

| | | |
|-------------------------|---|--|
| Model No. | WL-2400 Pro | |
| Capacity | 2048Wh | |
| Battery type | LiFeP04 | |
| Rated power | 2400W | |
| Peak power | 4800W | |
| AC output voltage range | 100-120V-/60Hz or 220-240V-/50H2 | |
| DC output | 2USB-C PD31 Max 140W 2*U5B-A QC3.0 | |
| XT60 output | 12V/30A | |
| Car charger output | 12V/10A | |
| Wireless charger output | 15W | |
| AC input | 80-135V/Max 1200W or 180-264V Max 1500W | |
| Solar/MPPT input(XT60) | 12-80V/20A Max 1200W | |
| Dimensions | 510*350*312mm | |
| Weight | 23.5kg | |
| APP | WiFi/Bluetooth Connection Available | |